

# FS 400 Heat Transfer Fluid

## Description

FS 400 Heat Transfer Fluid provides oxidation and thermal stability in vented systems at continuous temperatures up to 600°F (316°C). FS 400 Heat Transfer Fluid is formulated with materials that have fewer tendencies to form coke, lacquers, and other residues. FS 400 Heat Transfer Fluid is nontoxic.

Also available:

FS 450 Heat Transfer Fluid ISO 46

FS 500 Heat Transfer Fluid ISO 68

## Typical Properties

Test / Description	Specification
ISO Grade	32
Viscosity @ 100°C (cSt)	5.4
Viscosity @ 40°C (cSt)	32
Viscosity Index	102
Density (lb/gal)	7.21
CCS Viscosity (cP)	NA
Flash Point (°C)	215
Flash Point (°F)	419

## Product Availability

### FS 400 Heat Transfer Fluid ISO 32

5 Gal. Pail	Item #150835
55-gal. Drum	Item #151083
265-gal. Totes	Item #157519
Bulk	Item #227635

### FS 450 Heat Transfer Fluid ISO 46

55-gal. Drum	Item #227134
Bulk	Item #227133

### FS 500 Heat Transfer Fluid ISO 68

5 Gal. Pail	Item #208598
55-gal. Drum	Item #157707
265-gal. Totes	Item #157708
Bulk	Item #216912