

FS All-Purpose Gear Lube GL-5

Recommended Use:

All applications requiring GL-5 gear lubricant protection, including:

- Automotive differentials
- Manual transmissions
- Final drives
- Heavy-duty trucks
- Construction equipment
- Farm machinery
- Many other industrial applications

Meets or Exceeds:

- API Service GL-5
- MIL-L-2105D
- Mack GO-G, GO-H, GO-J
- US Steel 224
- AGMA 250.04 Specification, AGMA 9005-D94
- Case/IH MS-1316 (SAE 85W-140)
- Rockwell International 0-76-A (85W-140), 0-76 (80W-90)
- John Deere JDM J11E
- MT-1

Product Availability:

FS GL-5 80W-90 All Purpose Gear Oil

2 x 2.5 Gal.	Item #71255
5 Gal. Pail	Item #15235
55-gal. Drum	Item #71295
265-gal. Totes	Item #69810
Bulk	Item #71034

FS GL-5 85W-140 All Purpose Gear Oil

2 x 2.5 Gal.	Item #71256
5 Gal. Pail	Item #47323
55-gal. Drum	Item #71296
265-gal. Totes	Item #189609
Bulk	Item #71035

Typical Properties:

Test / Description	Specification	
	80W-90 (ISO 220)	85W-140 (ISO 460)
SAE Grade		
Viscosity @ 100°C (cSt)	20.0	28.2
Viscosity @ 40°C (cSt)	241.7	410.0
Viscosity Index	95	95
Density (lb/gal)	7.45	7.55
CCS Viscosity (cP)	NA	NA
Pour Point (°C)	-15	-9
Pour Point (°F)	5	16
Flash Point (°C)	205	220
Flash Point (°F)	401	428
AGMA Number	5	7
Timken OK Load (lbs)	45	45