

FS Ashless Natural Gas Engine Oil

Features

- Specially formulated for the most severe natural gas applications in **all makes of two-stroke natural gas-fired engines**
- Protects against high-temperature oxidation and nitration
- Provides superior protection against deposit formation
- Blended with high-quality, selected base oils and additives to provide superior engine cleanliness and extend oil life
- Superior cleanliness

Meets or Exceeds:

Primarily for use in all two-stroke applications, including:

- Cooper Bessemer
- Clark
- Ajax
- Superior

Always check owner's manual for proper recommendation.

Product Availability

| | |
|--------------|--------------|
| 5 Gal. Pail | Item #233865 |
| 55-gal. Drum | Item #202685 |
| Bulk | Item #159225 |

Typical Properties

| Test / Description | Specification | |
|-------------------------|---------------|-----------|
| SAE Grade | 30 | 40 |
| Viscosity @ 100°C (cSt) | 11.0 | 15.0 |
| Viscosity @ 40°C (cSt) | 99.5 | 156.5 |
| Viscosity Index | 95 | 95 |
| Density (lb/gal) | 7.34 | 7.39 |
| CCS Viscosity (cP) | NA | NA |
| Pour Point (°C) | -18 | -18 |
| Pour Point (°F) | 0 | 0 |
| Flash Point (°C) | 240 | 240 |
| Flash Point (°F) | 464 | 464 |