



FS CG 5400

Heavy Duty Grinding, Stamping, Machining, & Tapping Oil

FS CG 5400 is a straight oil formulation designed for extremely severe applications. The combination of high quality base oils and lubricity/ anti-weld additives enable **FS CG 5400** to excel in areas where many other products fail (especially when working with various grades of stainless and other hard materials). Parts will therefore run cooler, and tooling/ grinding wheels will need changing/ dressing less often.

TYPICAL PHYSICAL PROPERTIES:

Fluid Type:	Heavy Duty Oil
Specific Gravity:	0.91
Viscosity, cSt @ 40°C:	?????
Flash Point:	350°F
ASTM Color:	6.0 Brown
Copper Corrosion:	4A
Active Ingredients:	60%

STORAGE: **FS CG 5400** should be stored at room temperatures (between 55 to 95 °F). Keep away from sparks, open flames, and other sources of ignition as product and empty containers could contain combustible, flammable, or ignitable substances. Do not weld or cut empty drums.

HEALTH & SAFETY: Please refer to the Safety Data Sheet (SDS) for additional information.

Warranty: Because conditions of use are beyond our control no representation or warranty is made in connection with the use of this product. Technical information and recommendations are believed to be accurate but are not guaranteed.

June, 2015

R: Product Tech Letterhead 2015/FS CG 5400