

FS Concrete Form Oil

Description

FS Concrete Form Oil is a light-colored, nonstaining oil for use on concrete forms. This oil is formulated with a combination of spreading and release agents that provides even spreading of the oil on concrete forms and prevents cement from sticking to the forms. **FS Heavy Concrete Form Oil** can be prediluted up to 3:1 with No.1 fuel oil. **FS Light Concrete Form Oil** is prediluted. The optimal dilution ratio depends on trial and experience. Form oil improves the stripping of forms and extends form life by protecting wood surfaces and preventing rust on metal forms. It can be applied by brush or spray.

Typical Properties:

Test / Description	Specification		
	Light	Heavy	Proform
Viscosity @ 100°C (cSt)	NA	4.3	3.0
Viscosity @ 40°C (cSt)	1.5	22.0	12.5
Viscosity Index	NA	100	90
Density (lb/gal)	6.72	7.14	7.14
Pour Point (°C)	-54	-36	-21
Pour Point (°F)	-65	-33	-6
Flash Point (°C)	74	206	165
Flash Point (°F)	165	403	329

Product Availability:

FS Concrete Form Oil Light

5 Gal. Pail	Item #176320
55-gal. Drum	Item #071102
265-gal. Tank	Item #188082
Bulk Tank	Item #176362

FS Concrete Form Oil Proform

55-gal. Drum	Item #316495
265-gal. Tank	Item #316496
Bulk Tank	Item #316494

*Check price pages for item number.

FS Concrete Form Oil Heavy

5 Gal. Pail	Item #176321
55-gal. Drum	Item #167446
265-gal. Tank*	
Bulk Tank	Item #167557

