

FS Engine Guard SAE 20W-50 Premium Motor Oil

Description

FS Engine Guard SAE 20W-50 is formulated with highly refined base oil and a shear-stable viscosity index improver and utilizes an advanced detergent and dispersant package to provide excellent engine cleanliness. In addition, it contains wear control and friction modifiers, foam suppressants, corrosion inhibitors, and an antioxidant package.

Features and Benefits:

- Meets API category SJ
- High-detergent package for excellent engine cleanliness
- Contains higher levels of zinc to provide excellent anti-wear protection of critical engine parts
- High viscosity index that ensures easy cold starting and protective films that reduce viscosity breakdown
- High level of dispersancy that protects against sludge, engine rust, and corrosion under severe operating conditions
- Low volatility for reduced oil consumption and protection of emission-control system catalyst
- Formulated for turbocharged gasoline engines, high-performance street engines, cars, and pickups used for towing

Product Availability:

55-gal. Drum	Item #259608
Bulk	Item #259607

Typical Properties:

Test / Description	Specification
SAE Grade	20W-50
Viscosity @ 100°C (cSt)	21
Viscosity at 40°C (cSt)	180.5
Viscosity Index	138
Density (lb/gal)	7.33
CCS Viscosity (cP)	5,300
Pour Point (°C)	-21
Pour Point (°F)	-6
Flash Point (°C)	200
Flash Point (°F)	392
Zn (PPM)	1500