



# FS KOOL DRAW 1001E

## HIGH PERFORMANCE OIL

**FS Kool Draw 1001 E** is a highly compounded formulation made from vegetable-based oils and additives. This product provides superior performance on all ferrous and non-ferrous metals including stainless steel and yellow metals. **FS Kool Draw 1001 E** does NOT contain any mineral oil, chlorine, sulfur, or silicones; nor are there any ingredients recognized as hazardous by OSHA, CERLA/EPCRA: section 302, 311/12, and 313.

## PRODUCT APPLICATIONS

- Tube Bending
- Anti Splatter for Welding Applications (Will not smoke)
- Lubricity Aid in certain cutting oil operations
- Tapping/ Drilling Aid

## TYPICAL PHYSICAL PROPERTIES

- High heat capability (Flash point >350F)
- Little or no smoking tendencies
- Extremely good lubricity
- Will not stain ferrous, non-ferrous, or exotic metals and materials
- Non skin sensitizing
- Pleasant odor

**FS Kool Draw 1001 E** is designed to be used straight. Do not mix this product with water, oil, or solvent. Wash parts using standard cleaning methods.

**STORAGE:** **FS Kool Draw 1001E** should be stored at room temperatures (between 55 to 95 °F). Keep away from sparks, open flames, and other sources of ignition as product and empty containers could contain combustible, flammable, or ignitable substances. Do not weld or cut empty drums.

**HEALTH AND SAFETY:** Please refer to the Safety Data Sheet (SDS) for additional information.

**Warranty:** Because conditions of use are beyond our control no representation or warranty is made in connection with the use of this product. Technical information and recommendations are believed to be accurate but are not guaranteed.

June, 2015  
R: Product Tech Letterhead 2015/KD 1001 E