

# FS Low Ash Natural Gas Engine Oil

## Features

- Specially formulated for the most severe natural gas applications in all makes of natural gas fired engines
- Protects against high-temperature oxidation and nitration
- Provides superior protection against deposit formation
- Blended with high-quality, selected base oils and additives to provide superior engine cleanliness and extend oil life

## Meets or Exceeds:

- Caterpillar 3600 Series
- Caterpillar 3500 Series
- Waukesha 7044
- Waukesha 7042

Always check owner's manual for proper recommendation.

## Product Availability

### FS Low Ash 30

5 Gal. Pail

Item #200656

55-gal. Drum

Item #197353

Bulk

Item #159224

### FS Low Ash 40

55-gal. Drum

Item #213868

265-gal. Totes

Item #267852

Bulk

Item #182190

## Typical Properties

Test / Description	Specification			
SAE Grade	30	30/40	40	15W-40
Viscosity @ 100°C (cSt)	11	12.5	15.5	15
Viscosity @ 40°C (cSt)	95.5	120	165.5	115.5
Viscosity Index	100	95	95	135
Density (lb/gal)	28.7	28	27.8	29.5
CCS Viscosity (cP)	NA	NA	NA	6,100
Pour Point (°C)	-21	-21	-12	-24
Pour Point (°F)	-6	-6	10	-11
Flash Point (°C)	220	225	230	215
Flash Point (°F)	430	435	445	420
TBN	NA	NA	NA	NA
Sulfated Ash	0.35%	0.35%	0.35%	0.35%