

FS Suprex 15W-40, 10W-30, 10W, 20W-20, 30, 40, & 50

Description

Designed for heavy-duty two- and four-stroke diesel engines found in farm machinery, construction equipment, marine, and over-the-road use. Suprex can also be used as hydraulic fluid, especially in heavy-duty off-road equipment.

Blended using specially selected, high-quality base oils and additives providing excellent detergency, dispersancy, oxidation stability, rust/ corrosion prevention, and foam suppression.

Available in SAE viscosity grades 15W-40, 10W-30, 20W-20, 10W, 30, 40, and 50. Multi-viscosity 15W-40 and 10W-30 can eliminate seasonal grade changes in many areas and offer better fuel economy.

Meets or Exceeds:

- | | |
|---|---|
| <p>10W</p> <ul style="list-style-type: none"> • API CD-II • ACEA E3, B3, A3 <p>10W-30</p> <ul style="list-style-type: none"> • API CK-4 • API CJ-4 • API CI-4 <p>20W-20</p> <ul style="list-style-type: none"> • API CD-II <p>30</p> <ul style="list-style-type: none"> • API CF-2 • API CD-II • Caterpillar TO-2 <p>40</p> <ul style="list-style-type: none"> • API CF-2 • API CD-II • ACEA E3, B3, A3 <p>50</p> <ul style="list-style-type: none"> • API CF-2 • API CD-II | <p>15W-40</p> <ul style="list-style-type: none"> • API CK-4 • API CJ-4 • API CI-4 • API CG-4, CF-4 • API CD-II • API CF, CD, CE • API SL, SJ • MACK EO-M Plus • Caterpillar ECF-1 • ACEA A5 • ACEA E3, B3, A3 • Allison C-4 • Cummins 20077 • Mercedes Benz 288.3, 229.1 • Volvo VDS-2 • Global DHD-1 |
|---|---|

Product Availability

FS SUPREX SAE 15W-40			
Package Size	Item Number	Package Size	Item Number
5 Gal. Pail	155661	265-gal. Totes	15265
55-gal. Drum	15264	Bulk	15266

FS SUPREX SAE 10W-30			
Package Size	Item Number	Package Size	Item Number
5 Gal. Pail	302785	265-gal. Totes	302788
55-gal. Drum	302786	Bulk	167444

FS SUPREX SAE 10			
Package Size	Item Number	Package Size	Item Number
55-gal. Drum	15269	Bulk	15271
265-gal. Totes	15270		

FS SUPREX SAE 20W-20			
Package Size	Item Number	Package Size	Item Number
55-gal. Drum	15274	Bulk	15276
265-gal. Totes	15275		

FS SUPREX SAE 30			
Package Size	Item Number	Package Size	Item Number
2 x 2.5 Gal.	15278	265-gal. Totes	15281
55-gal. Drum	15280	Bulk	15282

FS SUPREX SAE 10W-30			
Package Size	Item Number	Package Size	Item Number
5 Gal. Pail	302785	265-gal. Totes	302788
55-gal. Drum	302786	Bulk	167444

FS SUPREX SAE 10W-30			
Package Size	Item Number	Package Size	Item Number
5 Gal. Pail	302785	265-gal. Totes	302788
55-gal. Drum	302786	Bulk	167444

Typical Properties

Test /Description	Specification						
SAE Grade	10	10W-30	15W-40	20W-20	30	40	50
Viscosity @ 100°C (cSt)	6.5	11.0	15.0	7.5	11.0	14.4	19.0
Viscosity @ 40°C (cSt)	39.7	71.2	111.0	49.4	92.0	135.0	214.0
Viscosity Index	115	145	140	115	105	105	100
Density (lb/gal)	7.23	7.20	7.28	7.23	7.29	7.39	7.46
CCS Viscosity (cP)	3,000	5,500	6,000	1,100	NA	NA	NA
Pour Point (°C)	-36	-33	-33	-33	-27	-18	-12
Pour Point (°F)	-33	-27	-27	-27	-17	0	10
Flash Point (°C)	180	210	215	205	220	220	225
Flash Point (°F)	356	410	419	401	428	428	437
TBN	10		10	10	9	10	10
Sulfated Ash	0.96%		0.96%	0.96%	0.96%	0.96%	0.96%
Color		L3.0					