



## FS ALL SEASON COOLANT/ANTIFREEZE Product Specification Sheet

### Features:

---

- Protection of cooling system metals from corrosion
- Protects aluminum from corrosion
- Protection against winter freeze-up or summer boil over
- Uniform heat transfer
- Non-foaming
- Safe on rubber hoses, water pumps, gaskets or exterior finishes
- Can be mixed with other brands of antifreeze

### Meets or exceeds performance requirements of:

---

- GM1899M
- GM1825M
- ASTM3306
- ASTM4985 (Cummins Service Bulletin 85T-2 and SAE J1034)

### Recommended for use in:

---

Can be used in both passenger cars and heavy-duty vehicles.

### Typical Specifications and Performance Data:

---

<b>Freezing Protection: 50% Antifreeze Solution °F</b>	-34
<b>Specific Gravity 60/60 F</b>	1.13
<b>Flash Point, °F, Min.</b>	250
<b>Color</b>	Green
<b>Equilibrium Boiling Point °F</b>	325 Min.
<b>Foam (ASTM D1881) Milliliters Increase Seconds, Break Time</b>	50 Max. 5 Max.
<b>Reserve Alkalinity</b>	10 Max.
<b>Water, %</b>	5 Max.
<b>ph: Concentrate 33.3% Antifreeze Solution</b>	10.0-10.9 10.0-10.5
<b>Antifreeze Glycols, %</b>	95 Min
<b>Anhydrous Alkali Metasilicate</b>	0.09%



**Product Availability:**

---

- 6 X 1 Gallon Cases
- 55 Gallon Drums Concentrate
- 55 Gallon Drums 50/50 Pre-Diluted

Reviewed December 2013