



FS MULTI VEHICLE ATF

FS Multi Vehicle Automatic Transmission Fluid (ATF) is a premium synthetic blend formulated to provide excellent service to a wide variety of transmission applications. FS Multi Vehicle ATF provides protection that meets or exceeds the quality standards in the industry. The advanced additive system protects against shudder and eliminates the need to stock ATF supplements. Carefully balanced friction modifiers maintain the smooth lockups required by many vehicles and provide friction retention for long-life performance. Enhanced oxidation, thermal stability, and corrosion resistance provide year-round protection of the transmission components.

Features:

- Protects metal parts from corrosion
- Provides excellent oxidative stability under severe conditions
- Reduces sludge and varnish buildup
- Protects transmission gears and allows them to operate smoothly
- Maintains lubricity
- Flows well for cold startup
- Provides excellent shift feel with no shudder
- Prevents fluid breakdown at higher operating temperatures
- Thoroughly field tested
- Performance surpasses minimum specifications

Recommended Use:

<u>Manufacturer</u>	<u>Fluid Specs</u>	<u>Manufacturer</u>	<u>Fluid Specs</u>
Allison	C-4	Ford	Mercon
Chrysler	ATF+ ATF+2	Ford	Mercon V
Chrysler	ATF+2	MAN	339 F
	Type 7176		
Chrysler	ATF+3	Mercedes	Pre-1996
Chrysler	ATF+4	Mitsubishi	Diamond SP-II
BMW	LA 2634	Mitsubishi	Diamond SP-III
BMW	LT 71141	Nissan/Infiniti	Matic-D
GM	Dexron	Nissan/Infiniti	Matic-J
GM	Dexron II	Toyota	Type-T
GM	Dexron II D	Toyota	Type T-III
GM	Dexron III H	Toyota-Lexus	Type T-IV



Recommended Use continued:

<u>Manufacturer</u>	<u>Fluid Specs</u>	<u>Manufacturer</u>	<u>Fluid Specs</u>
Honda	Premium	Voith	55.6335.32 (G607)
Honda	ATF -Z1	Volvo	Volvo
Kia, pre-2003 VW, Audi, Jeep, Mazda, Subaru, Suzuki, Isuzu, Hyundai, Daewoo			ZF TE-ML14B, ZF TE-ML 16L

- FS Multi Vehicle ATF cannot be used where Type F fluids are recommended.
- Should not be used in CVT transmissions.
- Should not be used in fill for life transmissions.
- Check owner's manual for these models: Pre-1971 Datsun/Nissan, Pre-1978 Lincolns, Pre-1981 Ford/Mercury, Pre-1983 Toyota, Pre-1985 Volvo, Pre-1986 Mazda, Pre-1993 Saab

Typical Specifications and Performance Data:

API Gravity	33.4
Appearance	Red
Specific gravity @ 15.6/15.6°C	0.858 typical
Weight per gallon (USA), lbs.	7.14
Viscosity @ 40°C, cSt	35
Viscosity @ 100°C, cSt	7.4
Viscosity Index	185
Pour Point, °C	-40
Flash Point, °C (°F) (PMCC)	150 (302) minimum

Product Availability:

- 12 × 1 qt.
- 5-gal. Pails
- 55-gal. Drums
- 265-gal. Mini-bulk
- Bulk